



**BREATHING SYSTEMS INC.**  
**8800 GROW DRIVE**  
**PENSACOLA, FL, 32514**  
**(850) 477-2324**



**BSI MODEL 5000 LIFE SUPPORT SYSTEM**  
**OPEN-CIRCUIT, PRESSURE-DEMAND, ENTRY AND ESCAPE, SELF-CONTAINED BREATHING APPARATUS AND**  
**COMBINATION, OPEN-CIRCUIT, PRESSURE-DEMAND, ENTRY AND ESCAPE, SELF-CONTAINED BREATHING APPARATUS**  
**AND TYPE C SUPPLIED-AIR RESPIRATOR**

THESE RESPIRATORS ARE APPROVED ONLY IN THE FOLLOWING CONFIGURATIONS:

**RESPIRATOR COMPONENTS**

TC-	Protection <sup>1</sup>	Helmet	Alternate Helmet Hose		Alternate Inline Filter	Primary Regulator	Secondary Regulator	Exhalation Valve	Interconnect Hose	Egress Reducer	Alternate Egress Cylinder		Alternate Safety Harness	Alternate Umbilical Hose Length				Emergency Egress Line	Cautions and Limitations <sup>2</sup>	
			500-017	215-061							215-062	215-003		215-004	215-001	215-022	200-010			200-005
13F-360	SA/SC/PD/ESC 5 min 2216 psi	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	DEJMNOS

**1 PROTECTON**

SA-Supplied Air    SC-Self-Contained    PD-Pressure Demand    ESC-Entry and Escape

**2 CAUTIONS AND LIMITATIONS**

- D Air-line respirators can be used only when the respirators are supplied with respirable air meeting the requirements of CGA G-7.1, Grade D or higher quality.
- E Use only the pressure ranges and hose lengths specified in the User Instructions.
- I - Contains electrical parts that may cause an ignition in flammable or explosive atmospheres.
- J - Failure to properly use and maintain this product could result in injury or death.
- M All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.
- N Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
- O Refer to User Instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
- S - Special or critical User Instructions and/or specific use limitations apply. Refer to User Instructions before donning.